



Model P125

The Edward Segal, Inc. **Model P125 Riveter** is one of the most modern and efficient riveters designed. A P125 is primarily engineered for 1/8" diameter semi-tubular rivets with a maximum length of 1/2", but also has the capacity to handle solid rivets, depending upon the diameter and material. This machine is simple to maintain; it is pneumatically powered, has only 8 moving parts, and a choice of feed systems depending on the size and shape of the rivets. The P125 is built around a steel weldment, and available as a pedestal or bench model, with several anvil brackets to accommodate a versatile range of parts.



8" Vibratory Bowl



Rotary Hopper

Features

- Pneumatically powered
- Standard 9" throat depth, optional upgrade to 18" or 24"
- Standard 2" stroke
- Available with either a rotary or vibratory feed system
- Safety device options include Ring Guard or Double Palm Buttons
- Simplistic controls, operator and service friendly
- May be configured with Multiple Heads

Optional Equipment

- Custom Part Fixtures
- Load Compensating Device
- Air Operated Anvil Pin
- Rivet Sensing
- Offset Tooling
- PLC Controls

Specifications

Dimensions:

- Bench: 10" W x 22" D x 24" H
- Pedestal: 28" W x 20" D x 61" H

Weight / Crated (approximate):

- Bench: 200 / 250 lbs.
- Pedestal: 550 / 600 lbs.

Electrical: 115 VAC 60 HZ, 1 Ph

Motor: None

Air: 0.1 CFM/cycle



360 Reynolds Bridge Road
Thomaston, CT 06787

Tel (860) 283-5821
Fax (860) 283-0871

Email: sales@edwardsegalinc.com
Web: www.edwardsegalinc.com



Proudly Made in the USA Since 1942

